

M1607

Smart module

M1607 is a low power and high performance module supporting 2G/3G/4G. It is a smart-based module with WIFI/BT/GNSS Receiver. It can fit application occasions that require android control center and datatransfer. M1607 has tiny package and wide work temperature. Its LCC package makes it easy to be soldered and produced quickly through standard SMT equipment. All of these features make it suit to industrial and domestic areas, such as smart measurement, wireless POS, law enforcement instrument, secure system, etc.



4 Core



LCC



Temperature
 -30°C to +75°C



WIFI(2.4G/5G)




BT 3.0/4.0



GNSS



Android



H.264 1080P



GPRS Class 12



2G/3G/4G

Main Features

- **OS:**
Android 6.0 (32bit)
- **Processor:**
Quad-core ARM@1.3GHz Cortex-A53 MPcore
512KB unified L2 cache
- **Memory:**
8GB eMMC+1GB LPDDR3 (Optional 16GB+2GB)
- **Graphics:**
MaliT720-MP@450MHz and 3D/100M tri/sec,
900M pixel/sec
- **Video:**
Decode H.264 1080P@30fps/40Mbps
Encode: H.264 1080P@30fps
- **Audio:**
Sampling rates: 8kHz to 192kHz
Sampling formats: 8/16/24-bit, Mono/Stereo
Speech codec(FR,HR,EFR,AMR FR,AMR HR
and Wide Band AMR)
- **Band:**
WCDMA:Band1/8
FDD_LTE:Band1/3/5/8
TDSCDMA:Band34/39
TDD_LTE:Band38/39/40/41
GSM/GPRS/EDGE: Band 3/8
- **Connectivity:**
WIFI: 802.11a/b/g/n
Bluetooth: BT3.0/4.0
GNSS: GPS/BEIDOU/Galileo/ Glonass
- **Sensor:**
Support 12 bit tri-axis accelerometer

Features for User Peripherals

- LCM: FHD (1920*1080)
- TP: Capacitive
- Front camera: 5MP
- Rear camera: 13MP
- Audio: 1 differential MIC input, 1 output

Specifications

- Voltage range: 3.50 to 4.35V (4V recommended)
- I/O voltage: 1.8V
- Package: 150-pin LCC
- Operating temperature range: -30 to +75°C
- Storage temperature range: -40 to +85°C
- Dimension: 40.0mm x 38.0mm x 3.0 mm
- 4 antenna PAD(SMD): WIFI/BT, GNSS, RF
Main antenna, RF MIMO antenna

Interfaces

- 2 SIM card (3.0V/1.8V)
- TF card
- USB 2.0 HS Peripheral (OTG)
- 4 UART
- 4 IIC
- SPI
- ADC
- GPIO
- EINT
- key
- Battery charge

